## We Claim As Our Invention:

A container comprising:

a first container portion having a wall defining an interior and an exterior of the first container portion; and

a second container portion having a wall defining an interior and an exterior of the second container portion, and a substantially open top portion, the exterior of the second container portion being spaced apart from the exterior of the first container portion via a connecting portion, the first container portion, second container portion and connecting portion being co-molded.

- The container of claim 1, wherein the first container portion has an inwardly directed depression formed in a lower portion of the wall of the first container portion.
- The container of claim 1, wherein the second container portion has an inwardly directed depression formed in a lower portion of the wall of the second container portion.
- The container of claim 1, wherein the connecting portion is formed at a height above the bottom of the first container portion.
- The container of claim 1, wherein the second container portion has at least one reinforcement formed in the wall of the second container portion.

- The container of claim 5, wherein the reinforcement comprises at least one rib formed in the wall of the second container portion.
- The container of claim 5, wherein the reinforcement comprises at least one crease formed in the wall of the second container portion.
- 8. The container of claim 5, wherein the reinforcement comprises a lip formed at or around a top of the wall of the second container portion.
- The container of claim 1, wherein the first container portion comprises a plurality of chambers.
- 10. The container of claim 1, wherein the first container portion comprises a handle.
- 11. The container of claim 1, wherein the connecting portion comprises at least one reinforcement formed therein.
  - 12. The container of claim 1, wherein the container is formed by blow-molding.
- 13. The container of claim 1, wherein the container is used with a material delivery device.
- 14. The container of claim 1, wherein the material delivery device is at least one of a spout extension, a spray nozzle and a funnel.

15. A method of forming a container, the method comprising the steps of:

co-molding a wall defining an interior and an exterior of a first container portion, a wall defining an interior and an exterior of a second container portion having a substantially open top portion, and a connecting portion integral to and spacing apart the exteriors of the first container portion and the second container portion.

- The method of claim 15, wherein the connecting portion is formed with at least one reinforcement therein.
  - 17. The method of claim 15, wherein the container is formed by blow molding.